




台灣 Lorric 噴嘴系列

標準扇形噴嘴	分佈形狀示意圖	H	AH NH	VH	V	產品特性
	 H,AH,NH 材質 AISI303 (不銹鋼) AISI316 (不銹鋼) BRASS (黃銅) HSS (硬化不銹鋼) PP					- 具有強大的沖擊力與均勻性。 - 噴霧粒徑大小適中，噴灑為扇形分佈。 - 六角板手設計，安裝簡單，不耗力，不易變形。 - 公差：± 5%。 產品用途 - PCB 電路板剝膜制程、高壓清洗、粉塵碎石洗淨、氣態洗滌、溶液散佈、潤濕、鋼鐵冷卻、消防水霧。
		角度：65,80,90 度 特殊 0.15,25,40,50,100,110 度				

流量表				
	H	AH/NH	VH	V

型號	牙規 (BSPT)			不同壓力 (kg / cm ²) 下之對應流量 (LPM)						
	1/8"	1/4"	3/8"	0.5	1.0	2.0	3.0	4.0	5.0	6.0
01	●	●		0.16	0.23	0.32	0.39	0.45	0.50	0.55
2.5	●	●		0.40	0.57	0.80	0.98	1.13	1.27	-
03	●	●		0.48	0.68	0.96	1.17	1.35	1.51	1.66
04	●	●		0.64	0.90	1.28	1.56	1.81	2.02	2.21
4.5	●	●		0.72	1.02	1.44	1.76	2.03	2.27	-
05	●	●		0.80	1.13	1.60	1.96	2.26	2.52	2.76
06	●	●		0.96	1.35	1.92	2.35	2.71	3.03	3.32
07	●	●		1.19	1.58	2.23	2.74	3.16	3.53	-
7.5	●	●		1.20	1.69	2.39	2.93	3.38	3.78	-
08	●	●		1.28	1.81	2.55	3.13	3.61	4.04	4.42
10	●	●		1.60	2.26	3.19	3.91	4.52	5.05	5.53
12.5	●	●		2.00	2.82	3.99	4.89	5.64	6.31	6.91
15	●	●		2.40	3.39	4.79	5.87	6.77	7.57	8.29

- ☆ 建議操作壓力 3 kg / cm²。
- ☆ AH, NH 具有兩個平行面，安裝時更易於排列定位。小流量建議使用。
- 附註：相同流量的噴嘴，角度越小衝擊力越大。




尺寸規格 (mm)

系列	牙規 (BSPT)	A	B	C
H	1/8" (金屬)	12	12	19
	1/4" (金屬)	14	15	26
	3/8" (金屬)	18	15	30
AH NH	1/8" (PP)	11.75	10.3	19
	1/4" (PP)	13.7	13.7	25
	3/8" (金屬)	18	15	30
VH	1/8" (PVDF)	11.8	10.3	19
	1/4" (PVDF)	15	10.5	21.4
	3/8" (PVDF)	16.7	13	24.6
V	1/4" (PVDF)	14	13.7	25

訂購範例：

尺寸	系列	流量代號	角度	材質
1/4"	H	10	65	AISI316

快拆式扇形噴嘴	分佈形狀示意圖	QFH	QFYH	QSH	產品特性
	 材質 QFH : PVDF QFYH, QSH : PP				- 可以提高沖擊力，減少霧化的發生。 - 兩件式設計，噴嘴可以精確的旋入定位點，維持噴霧的均一性，確保生產品質。 - 墊圈材質可分為 EPDM、VITON 兩種。 - QF 系列與 QS 系列本體無法共享。 - 噴嘴乃雙翼構造，徒手即可拆裝噴嘴。 產品用途 - 清洗、洗淨、潤濕、散佈、冷卻、水幕等工業用需求。
		角度：65,80,90 度 特殊 45,100,110 度			

流量表			
	QFH	QFYH	QSH

流量代碼	不同壓力 (kg / cm ²) 下之對應流量 (LPM)						
	0.5	1.0	2.0	3.0	4.0	5.0	6.0
02	0.32	0.45	0.64	0.78	0.90	1.01	1.11
2.5	0.40	0.57	0.80	0.98	1.13	1.27	-
03	0.48	0.68	0.96	1.17	1.35	1.51	1.66
04	0.64	0.90	1.28	1.56	1.81	2.02	2.21
05	0.80	1.13	1.60	1.96	2.26	2.52	2.76
06	0.96	1.35	1.92	2.35	2.71	3.03	3.32
07	1.12	1.58	2.23	2.74	3.16	3.53	-
7.5	1.20	1.69	2.39	2.93	3.38	3.78	-
08	1.28	1.81	2.55	3.13	3.61	4.04	4.42
09	1.44	2.03	2.87	3.52	4.06	4.54	-
10	1.60	2.26	3.19	3.91	4.52	5.05	5.53
12.5	2.00	2.82	3.99	4.89	5.64	6.31	6.91
15	2.40	3.39	4.79	5.87	6.77	7.57	8.29
20	3.19	4.52	6.39	7.82	9.03	10.10	11.06

各系列噴嘴在建議操作壓力下，可供選擇之角度：65° 80° 90°。



特殊噴嘴角度：45° 100° 110° 請先來電洽詢。

尺寸規格 (mm)

系列	牙規 (BSPT)	A	B	C
QFH	1/8"	32	27.5	39
	1/4"	32	27.5	42.6
	3/8"	32	27.5	42.6
QFYH	1/8"	36	27.5	39
	1/4"	36	27.5	42.6
QSH	1/4"	31.5	30.5	44.2
	3/8"	31.5	30.5	44.2

訂購範例：

尺寸	系列	流量代號	角度	材質
1/4"	QFH	08	80	PVDF
1/8"	QFYH	06	65	PP

多件式扇形噴嘴	分佈形狀示意圖	KAD	DVEH	CH	產品特性
	 KAD,CH 材質 AISI303 (不銹鋼) AISI316 (不銹鋼) BRASS (黃銅) HSS (硬化不銹鋼)		螺帽：PP 底座：UPVC 噴嘴：PVDF 		- 具有強大的沖擊力與均勻性。 - 噴霧粒徑大小適中，噴灑為扇形分佈。 - 多件式構造，方便清洗與更換。 - 公差：± 5%。 產品用途 - 適用於清洗、洗淨、潤濕、散佈、冷卻、水幕等工業用需求。
		角度：65,80,90 度 特殊 45,100,110 度			